



TECHNICAL DATA

| | |
|--|---|
| According Standard | EN-61.558-2-4 |
| Rated Power | 200 VA |
| Primary Voltage | 690V |
| Secondary Voltage | 230V |
| Frequency | 50/60 Hz |
| Protection Grade | IP-00 |
| Isolement Level | F |
| ED: | 100% |
| ta | 40°C |
| Class | I |
| Strength Dielectric test between live parts | 5.000V |
| Strength Dielectric test between live parts and mass | 3.500V |
| Data Plate | Yes |
| Electrostatic screen | Non |
| Wound wires | Cooper wire G-2 class H |
| Magnetic Core | Non oriented grain, cold lamination. M 330-50A EN10106 |
| Bobbin | PA6 + Glass Fiber (30%) |
| Type Refrigeration | Dry |
| Connection | |
| Terminal block | 4mm (PRI) 4mm (SEC) |
| Weight | 2,7 Kg. |

Drew by:

Miguel A. Hdez. - 23/09/2022

Approved by:

Victor Gallego - 23/09/2022

SINGLE PHASE ISOLATION TRANSFORMER



Units:
mm.

TA001209700

Page 1 de 1
Rev: 01
Rev date.: 23/09/2022

MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias
50450-MUEL, SPAIN - VAT ESB50040146
Tel +34 976 140606 - Fax +34 976 140 607
comercial@manumag.com, export@manumag.com

