



TECHNICAL DATA

According Standard	EN-61.558-2-4
Rated Power	2500 VA
Primary Voltage	400V
Secondary Voltage	230V
Frequency	50/60 Hz
Protection Grade	IP-00
Isolement Level	F
ED:	100%
ta	40°C
Class	I
Strength Dielectric test between live parts	4.600V
Strength Dielectric test between live parts and mass	3.500V
Data Plate	Yes
Electrostatic screen	Non
Wound wires	Cooper wire G-2 class H
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106
Bobbin	PA6 + Glass Fiber (30%)
Type Refrigeration	Dry
Connection	
Terminal block	4mm (PRI) + faston 4mm (SEC) + faston
Weight	17,8 Kg.

Drew by: Miguel A. Hdez. - 26/09/2022
 Approved by: Victor Gallego - 26/09/2022

SINGLE PHASE ISOLATION TRANSFORMER

Units: mm. TA002255400

Page 1 de 1
 Rev: 01
 Rev date.: 26/09/2022

manumag

MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias
 50450-MUEL, SPAIN - VAT ESB50040146
 Tel +34 976 140606 - Fax +34 976 140 607
 comercial@manumag.com, export@manumag.com