



TECHNICAL DATA

|  |   |
|--|---|
| According Standard                                   | EN-61.558-2-4   |
| Rated Power  | 4000 VA   |
| Primary Voltage                                      | 690V  |
| Secondary Voltage                                    | 230V  |
| Frequency  | 50/60 Hz  |
| Protection Grade                                     | IP-00   |
| Isolement Level                                      | F   |
| ED:  | 100%  |
| ta   | 40°C  |
| Class  | I   |
| Strength Dielectric test between live parts          | 5.000V  |
| Strength Dielectric test between live parts and mass | 3.500V  |
| Data Plate   | Yes   |
| Electrostatic screen                                 | Non   |
| Wound wires  | Cooper wire G-2 class H                                   |
| Magnetic Core  | Non oriented grain, cold lamination.<br>M 330-50A EN10106 |
| Bobbin   | PA6 + Glass Fiber (30%)                                   |
| Type Refrigeration                                   | Dry   |
| Connection   |   |
| Terminal block                                       | 4mm (PRI) + faston<br>4mm (SEC) + faston                  |
| Weight   | 25,3 Kg.  |

Drew by: Miguel A. Hdez. - 27/09/2022  
 Approved by: Victor Gallego - 27/09/2022

SINGLE PHASE ISOLATION TRANSFORMER

Units: mm. TA002409700

Page 1 de 1  
 Rev: 01  
 Rev date.: 27/09/2022

**manumag**

MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias  
 50450-MUEL, SPAIN - VAT ESB50040146  
 Tel +34 976 140606 - Fax +34 976 140 607  
 comercial@manumag.com, export@manumag.com