



TECHNICAL DATA

According Standard	EN-61.558-2-4
Rated Power	5000 VA
Primary Voltage	400V
Secondary Voltage	230V
Frequency	50/60 Hz
Protection Grade	IP-00
Isolement Level	F
ED:	100%
ta	40°C
Class	I
Strength Dielectric test between live parts	4.600V
Strength Dielectric test between live parts and mass	3.500V
Data Plate	Yes
Electrostatic screen	Non
Wound wires	Cooper wire G-2 class H
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106
Bobbin	PA6 + Glass Fiber (30%)
Type Refrigeration	Dry
Connection	
Terminal block	10mm (PRI) 10mm (SEC)
Weight	30 Kg.

Drew by: Miguel A. Hdez. - 27/09/2022	Approved by: Victor Gallego - 27/09/2022	
SINGLE PHASE ISOLATION TRANSFORMER		
Units: mm.	TA002505400	
Page 1 de 1 Rev: 01 Rev date.: 27/09/2022	MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias 50450-MUEL, SPAIN - VAT ESB50040146 Tel +34 976 140606 - Fax +34 976 140 607 comercial@manumag.com, export@manumag.com	