



TECHNICAL DATA

According Standard	EN-61.558-2-13
Rated Power	1500 VA
Primary Voltage	125/220V
Secondary Voltage	125/220V
Frequency	50/60 Hz
Protection Grade	IP-20
Isolement Level	F
ED:	100%
ta	40°C
Class	I
Strength Dielectric test between live parts	-
Strength Dielectric test between live parts and mass	2.300V
Data Plate	Yes
Electrostatic screen	Non
Wound wires	Aluminium wire G-2 class H
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106
Bobbin	PA6 + Glass Fiber (30%)
Type Refrigeration	Dry
Connection	-
Terminal block	TEKOX 16mm (PRI) TEKOX 16mm (SEC)
Weight	5,75 Kg.

Drew by:

Miguel A. Hdez. - 26/09/2023

Approved by:

Victor Gallego - 26/09/2023

STEP UP-DOWN I-PHASE
AUTOTRANSFORMER



Units:
mm.

AMN02215201

Page 1 de 1
Rev: 01
Rev date.: 26/09/2023

MANUMAG SL - C/Antonio Barriendas s/n, Pol. Ind. Las Norias
50450-MUEL, SPAIN - VAT ESB50040146
Tel +34 976 140606 - Fax +34 976 140 607
comercial@manumag.com, export@manumag.com

manumag