



### TECHNICAL DATA

According Standard	EN-61.558-2-13
Rated Power	7500 VA
Primary Voltage	110/220V
Secondary Voltage	110/220V
Frequency	50/60 Hz
Protection Grade	IP-20
Isolement Level	F
ED:	100%
ta	40°C
Class	I
Strength Dielectric test between live parts	-
Strength Dielectric test between live parts and mass	2.300V
Data Plate	Yes
Electrostatic screen	Non
Wound wires	Aluminium wire G-2 class H
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106
Bobbin	PA6 + Glass Fiber (30%)
Type Refrigeration	Dry
Connection	-
Terminal block	TEKOX 25mm (PRI) Tekox 25mm (SEC)
Weight	18,3 Kg.

Drew by:

Miguel A. Hdez. - 28/09/2023

Approved by:

Victor Gallego - 28/09/2023

STEP UP-DOWN I-PHASE  
AUTOTRANSFORMER



Units:  
mm.

AMN02275041

Page 1 de 1  
Rev: 01  
Rev date.: 28/09/2023

MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias  
50450-MUEL, SPAIN - VAT ESB50040146  
Tel +34 976 140606 - Fax +34 976 140 607  
comercial@manumag.com, export@manumag.com

