



TECHNICAL DATA

According Standard	EN-61.558-2-13	
Rated Power	5000 VA	
Primary Voltage	110/240V	
Secondary Voltage	110/240V	
Frequency	50/60 Hz	
Protection Grade	IP-20	
Isolement Level	F	
ED:	100%	
ta	40°C	
Class	I	
Strength Dielectric test between live parts	-	
Strength Dielectric test between live parts and mass	2.750V	
Data Plate	Yes	
Electrostatic screen	Non	
Wound wires	Aluminium wire G-2 class H	
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106	
Bobbin	PA6 + Glass Fiber (30%)	
Type Refrigeration	Dry	
Connection	-	
Terminal block	TEKOX 16mm (PRI) TEKOX 16mm (SEC)	
Weight	13 Kg.	
Drew by: Miguel A. Hdez. - 21/11/2023	Approved by: Victor Gallego - 21/11/2023	
STEP UP-DOWN I-PHASE AUTOTRANSFORMER		
Units: mm.	ARB02250061	
Page 1 de 1 Rev: 01 Rev date.: 21/11/2023	MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias 50450-MUEL, SPAIN - VAT ESB50040146 Tel +34 976 140606 - Fax +34 976 140 607 comercial@manumag.com, export@manumag.com	