



TECHNICAL DATA	
According Standard	EN-61.558-2-4
Rated Power	100 VA
Primary Voltage	230V
Secondary Voltage	230V + N
Frequency	50/60 Hz
Protection Grade	IP-00
Isolement Level	F
ED:	100%
ta	40°C
Class	I
Strength Dielectric test between live parts	3.500V
Strength Dielectric test between live parts and mass	3.500V
Data Plate	Yes
Electrostatic screen	Non
Wound wires	Cooper wire G-2 class H
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106
Bobbin	PA6 + Glass Fiber (30%)
Type Refrigeration	Dry
Connection	
Terminal block	4mm FASTON (PRI) 4mm FASTON (SEC)
Weight	1,8 Kg.
Drew by: Miguel A. Hdez. - 05/09/2023	Approved by: Victor Gallego - 05/09/2023
SINGLE PHASE ISOLATION TRANSFORMER	
Units: mm.	TNA01103200
Page 1 de 1 Rev: 01 Rev date.: 05/09/2023	MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias 50450-MUEL, SPAIN - VAT ESB50040146 Tel +34 976 140606 - Fax +34 976 140 607 comercial@manumag.com, export@manumag.com