



TECHNICAL DATA		
According Standard	EN-61.558-2-4	
Rated Power	160 VA	
Primary Voltage	220/380/440/460/480V	
Secondary Voltage	110/220V	
Frequency	50/60 Hz	
Protection Grade	IP-00	
Isolement Level	F	
ED:	100%	
ta	40°C	
Class	I	
Strength Dielectric test between live parts	4.900V	
Strength Dielectric test between live parts and mass	3.500V	
Data Plate	Yes	
Electrostatic screen	Non	
Wound wires	Cooper wire G-2 class H	
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106	
Bobbin	PA6 + Glass Fiber (30%)	
Type Refrigeration	Dry	
Connection		
Terminal block	4mm FASTON (PRI) 4mm FASTON (SEC)	
Weight	2,5 Kg.	
Drew by: Miguel A. Hdez. - 12/09/2023	Approved by: Victor Gallego - 12/09/2023	
SINGLE PHASE ISOLATION TRANSFORMER		
Units: mm.	<b>TSC51162200</b>	
Page 1 de 1 Rev: 01 Rev date.: 12/09/2023	MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias 50450-MUEL, SPAIN - VAT ESB50040146 Tel +34 976 140606 - Fax +34 976 140 607 comercial@manumag.com, export@manumag.com	