



### TECHNICAL DATA

According Standard	EN-61.558-2-4
Rated Power	250 VA
Primary Voltage	220/380/440/460/480V
Secondary Voltage	110/220V
Frequency	50/60 Hz
Protection Grade	IP-00
Isolement Level	F
ED:	100%
ta	40°C
Class	I
Strength Dielectric test between live parts	4.900V
Strength Dielectric test between live parts and mass	3.500V
Data Plate	Yes
Electrostatic screen	Non
Wound wires	Cooper wire G-2 class H
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106
Bobbin	PA6 + Glass Fiber (30%)
Type Refrigeration	Dry
Connection	
Terminal block	4mm FASTON (PRI) 4mm FASTON (SEC)
Weight	3,9 Kg.

Drew by:

Miguel A. Hdez. - 12/09/2023

Approved by:

Victor Gallego - 12/09/2023

SINGLE PHASE ISOLATION  
TRANSFORMER



Units:  
mm.

TSC51252200

Page 1 de 1  
Rev: 01  
Rev date.: 12/09/2023

MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias  
50450-MUEL, SPAIN - VAT ESB50040146  
Tel +34 976 140606 - Fax +34 976 140 607  
comercial@manumag.com, export@manumag.com

**manumag**