



TECHNICAL DATA

| | |
|---|---|
| According Standard | EN-61.558-2-4 |
| Rated Power | 5 KVA |
| Primary Voltage | 400V |
| Secondary Voltage | 690V+N |
| Frequency | 50/60 Hz |
| Protection Grade | IP-00 |
| Isolement Level | F |
| ED: | 100% |
| ta | 40°C |
| Class | I |
| Strength Dielectric test between live parts | 4.600V |
| Strength Dielectric test between live parts and mass | 2.300V |
| Data Plate | Yes |
| Electrostatic screen | Non |
| Wound wires | Cooper wire class H |
| Magnetic Core | Non oriented grain, cold lamination. M 330-50A EN10106 |
| Bobbin | PA6 + Glass Fiber (30%) |
| Type Refrigeration | Dry |
| Connection | Dyn |
| Terminal block | CONTA CLIP 10mm (PRI) CONTA CLIP 10mm (SEC) |
| Weight | 40 Kg. |

Drew by:

Miguel A. Hdez. - 10/11/2023

Approved by:

Victor Gallego - 10/11/2023

THREE PHASE ISOLATION
TRANSFORMER



Units:
mm.

YA002507360

Page 1 de 1
Rev: 01
Rev date.: 10/11/2023

MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias
50450-MUEL, SPAIN - VAT ESB50040146
Tel +34 976 140606 - Fax +34 976 140 607
comercial@manumag.com, export@manumag.com

manumag