



TECHNICAL DATA

| | |
|--|---|
| According Standard | EN-61.558-2-4 |
| Rated Power | 7,5 KVA |
| Primary Voltage | 400V |
| Secondary Voltage | 230V + N |
| Frequency | 50/60 Hz |
| Protection Grade | IP-23 |
| Isolement Level | F |
| ED: | 100% |
| ta | 40°C |
| Class | I |
| Strength Dielectric test between live parts | 4.600V |
| Strength Dielectric test between live parts and mass | 3.500V |
| Data Plate | Yes |
| Electrostatic screen | Non |
| Wound wires | Enamelled cooper wire class H |
| Magnetic Core | Non oriented grain, cold lamination. M 330-50A EN10106 |
| Bobbin | PA6 + Glass Fiber (30%) |
| Type Refrigeration | Dry |
| Connection | Dyn |
| Terminal block | CONTA CLIP 10mm |
| Weight | 60 Kg. |

| | | |
|---|---|--|
| Drew by: Miguel A. Hdez. - 30/10/2023 | Approved by: Victor Gallego - 30/10/2023 | |
| THREE-PHASE ISOLATION TRANSFORMER | | |
| Units: mm. | YAQ02755463 | |
| Page 1 de 1 Rev: 01 Rev date.: 30/10/2023 | MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias 50450-MUEL, SPAIN - VAT ESB50040146 Tel +34 976 140606 - Fax +34 976 140 607 comercial@manumag.com, export@manumag.com | |