



TECHNICAL DATA

According Standard	EN-61.558-2-4
Rated Power	125 KVA
Primary Voltage	400V
Secondary Voltage	690V + N
Frequency	50/60 Hz
Protection Grade	IP-23
Isolement Level	F
ED:	100%
ta	40°C
Class	I
Strength Dielectric test between live parts	4.600V
Strength Dielectric test between live parts and mass	3.500V
Data Plate	Yes
Electrostatic screen	Non
Wound wires	Enamelled cooper wire class H
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106
Bobbin	PA6 + Glass Fiber (30%)
Type Refrigeration	Dry
Connection	Dyn
Terminal block	CONTA CLIP m12
Weight	380 Kg.

Drew by: Miguel A. Hdez. - 02/11/2023	Approved by: Victor Gallego - 02/11/2023	
THREE-PHASE ISOLATION TRANSFORMER		
Units: mm.	YAQ04127363	
Page 1 de 1 Rev: 01 Rev date.: 02/11/2023	MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias 50450-MUEL, SPAIN - VAT ESB50040146 Tel +34 976 140606 - Fax +34 976 140 607 comercial@manumag.com, export@manumag.com	