



TECHNICAL DATA

Accordinging Standard	EN-61.558-2-4
Rated Power	5 KVA
Primary Voltage	400V (III)
Secondary Voltage	230V (I)
Frequency	50/60 Hz
Protection Grade	IP-23
Isolement Level	F
ED:	100%
ta	40°C
Class	I
Strength Dielectric test between live parts	4.600V
Strength Dielectric test between live parts and mass	3.500V
Data Plate	Yes
Electrostatic screen	Non
Wound wires	Cooper wire G-2 class H
Magnetic Core	Non oriented grain, cold lamination. M 330-50A EN10106
Bobbin	PA6 + Glass Fiber (30%)
Type Refrigeration	Dry
Connection	V-v inv.
Terminal block	CONTACLIP 10mm
Weight	39 Kg.

Drew by: Miguel A. Hdez. - 09/05/2023	Approved by: Victor Gallego - 09/05/2023	
THREE PHASE-SINGLE PHASE ISOLATION TRANSFORMER		
Units: mm.	YZV02505403	
Page 1 de 1 Rev: 01 Rev date.: 09/05/2023	MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias 50450-MUEL, SPAIN - VAT ESB50040146 Tel +34 976 140606 - Fax +34 976 140 607 comercial@manumag.com, export@manumag.com	