



TECHNICAL DATA

| | |
|--|---|
| According Standard | EN-61.558-2-13 |
| Rated Power | 500 VA |
| Primary Voltage | 230/400V |
| Secondary Voltage | 230/400V |
| Frequency | 50/60 Hz |
| Protection Grade | IP-20 |
| Isolement Level | F |
| ED: | 100% |
| ta | 40°C |
| Class | I |
| Strength Dielectric test between live parts | - |
| Strength Dielectric test between live parts and mass | 2.300V |
| Data Plate | Yes |
| Electrostatic screen | Non |
| Wound wires | Aluminium wire G-2 class H |
| Magnetic Core | Non oriented grain, cold lamination. M 330-50A EN10106 |
| Bobbin | PA6 + Glass Fiber (30%) |
| Type Refrigeration | Dry |
| Connection | - |
| Terminal block | TEKOX 10mm (PRI) TEKOX 10mm (SEC) |
| Weight | 3,1 Kg. |

Drew by:

Miguel A. Hdez. - 09/01/2024

Approved by:

Victor Gallego - 09/01/2024

STEP UP-DOWN I-PHASE
AUTOTRANSFORMER



Units:
mm.

AMD02150621

Page 1 de 1
Rev: 01
Rev date.: 09/01/2024

MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias
50450-MUEL, SPAIN - VAT ESB50040146
Tel +34 976 140606 - Fax +34 976 140 607
comercial@manumag.com, export@manumag.com

