



### TECHNICAL DATA

|  |   |
|--|---|
| According Standard                                   | EN-61.558-2-15  |
| Rated Power  | 10000 VA  |
| Primary Voltage                                      | 400V+N  |
| Secondary Voltage                                    | 230V  |
| Frequency  | 50/60 Hz  |
| Protection Grade                                     | IP-00   |
| Isolement Level                                      | F   |
| ED:  | 100%  |
| ta   | 40°C  |
| Class  | I   |
| Strength Dielectric test between live parts          | 4.500V  |
| Strength Dielectric test between live parts and mass | 4.500V  |
| Data Plate   | Yes   |
| Electrostatic screen                                 | Yes   |
| Wound wires  | Cooper wire G-2 class H                                   |
| Magnetic Core  | Non oriented grain, cold lamination.<br>M 330-50A EN10106 |
| Bobbin   | PA6 + Glass Fiber (30%)                                   |
| Type Refrigeration                                   | Dry   |
| Connection   | YNd11   |
| Terminal block                                       | CONTA CLIP 10mm (PRI)<br>CONTA CLIP 10mm (SEC)            |
| Weight   | 62 Kg.  |

Drew by:

Miguel A. Hdez. - 02/02/2024

Approved by:

Victor Gallego - 02/02/2024

III-PHASE TRANSFORMER FOR MEDICAL LOCATIONS



Units:  
mm.

YD003105440

Page 1 de 1  
Rev: 01  
Rev date.: 02/02/2024

MANUMAG SL - C/Antonio Barriendos s/n, Pol. Ind. Las Norias  
50450-MUEL, SPAIN - VAT ESB50040146  
Tel +34 976 140606 - Fax +34 976 140 607  
comercial@manumag.com, export@manumag.com

